



1430-AW30F length 500mm
套PVC管, L=50mm

Specifications:

PHASE	STEP ANGLE	CONNECTION STYLE	CURRENT	RESISTANCE	INDUCTANCE	HOLDING TORQUE	ROTOR INERTIA	WEIGHT
	DEG/STEP		A	ohms	mH	N.m	gcm ²	Kg
4	1.8	parallel	6	0.63	8	12	4000	5.3
		series	3	2.5	32			
		unipolar	4.2	1.25	8	8.4		

X. \pm 0.1	X° \pm 1°	UNITS	mm	NAME (INTENDED USE)	<p>雷赛智能 Leadshine</p>						
.X \pm 0.05	.X° \pm 0.5°	MAT'L		PART NO. (INTENDED USE)		TITLE: 86HS120					
.XX \pm 0.02	.XX° \pm 0.2°	FINISH		APPD:		DWG NO.:					
.XXX \pm 0.005	.XXX° \pm 0.05°	Q'TY		CHKD:							
<small>THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF CHINA LEADSHINE TECHNOLOGY CO., LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF CHINA LEADSHINE TECHNOLOGY CO., LTD.</small>				DR:	<table border="1"> <tr> <td>SCALE</td> <td>SHEET</td> <td>REV.</td> </tr> <tr> <td>1/1</td> <td>2/2</td> <td></td> </tr> </table>	SCALE	SHEET	REV.	1/1	2/2	
SCALE	SHEET	REV.									
1/1	2/2										